

## 985S Super Suds Vehicle Wash Detergent

### Product Description

985S Super Suds (985S) is a high performance, liquid soap formulated for use in brush cleaning systems or pressure spray wash systems. 985S provides excellent hard water control and is completely soluble in hot or cold water. 985S provides superior soil cutting ability without the danger of staining, corrosion, or discoloration on vehicle surfaces.

### Performance Features

- Lifts Stubborn Traffic Film, Oil, Grease, Residue, and Grime from Vehicles Surface
- Biodegradable And Environmentally Green
- Contains NO Polluting Phosphates
- Will Not Attack Paint or Rubber Seals
- Multi-Metal Safe / Use Anywhere Water is Tolerable
- Super Concentrated Formula For Low Volume Usage And Low Cost
- Excellent in Hard Water

### Physical Specifications

Physical State	Liquid
Appearance	Amber
pH	≈ Neutral
Rinseability	Excellent
Fragrance	Lemon Lime

### Equipment Requirements

985S is safe for use with all standard car wash equipment.

### Product Make-Up

985S is a concentrated vehicle soap. Dilute with water to achieve specified strength concentrations.

### Concentration and Application Methods

#### Automatic Car Wash Systems

Add 985S directly to concentrate tank or meter directly into water flow. 985S strength concentration should be 1/2 to 4 oz./gallon of water. The use of HOT water increases performance. Apply to the surface to be cleaned with high / low pressure spray. Follow with a thorough water rinse.

## Technical Data Sheet

### Vehicle Washing

SPONGE, BRUSH & BUCKET: For typical vehicle, truck or fleet washing, add 5%-10% by volume of 985S to a water-filled bucket at a temperature between 40°–160° F. Apply to surface to be cleaned with sponge or brush. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse.

### **Companion Products**

See Seacole's Auto, Bus, Truck, RV, and Marine product line.

### **Safety and Handling**

Read and understand this products MSDS before handling.

### **Waste Treatment**

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

### **Ordering Information**

985S is available in 5 gallon pails, 30 gallon drums, and 55 gallon drums.



**SeacoleERC**

[Environmentally Responsible Chemistry]

13505 Industrial Park Blvd. Plymouth, MN 55441