

810 Cooling System Corrosion Inhibitor

Product Description

810 is a powdered, multi-metal safe corrosion inhibitor for use in diesel engine cooling systems to protect from premature failure due to corrosion. 810 is a free-flowing powder capable of being added directly into filler necks of cooling water systems. 810 dissolves quickly in warm water and will not freeze in cold weather months. Fifteen pounds is sufficient to treat any common locomotive cooling system (275-350 gallons).

Performance Features

- Inhibits corrosion of all metals including: 30/70A Solder, Brass, Copper, Steel, Cast Iron, Cast Aluminum and 85/15 Brass (EMD), at levels of 1 pound per 20 gallons. Proprietary blend of nitrite and other organic and inorganic inhibitors protects all the metals found in locomotive cooling systems. Controls scale and deposits.
- Conforms to the ASTM D1384 Specification, the GETS 84A231282 Specification dated 04-19-2012, Rev. O (Locomotive Coolant) and the EMD MI 1748 Section 6.1.1 dated 05-15-2009, Rev. G (Locomotive Coolant) Specification, for Corrosion Resistance.
- Conforms to the ASTM D1418 Specification, the GETS 84A231282 Table 4, O-rings Specification and EMD MI 1748 Section 6.1.2.2, Seals Specification, for Elastomer Chemical Resistance testing.
- Does Not Contain Chromate Or Zinc Metal Compounds
- Used Solutions of 810 Are Normally Regarded As Non-Regulated And Biodegradable Upon Disposal
- Contains Boron As A Tracer Element To Simplify Detection Of Coolant Contamination in Engine Oil
- Can Be Used With Ethylene Glycol Based Antifreezes

Physical Specifications

Physical State	Powder
Appearance	Red & White Mottled
Rinseability	Excellent
pH (2% Solution)	< 10.5

Equipment Requirements

810 is safe for use with all diesel engine cooling systems. Do NOT use in gasoline engines.

Product Make-Up

810 is packaged ready-to-use.

Technical Data Sheet

Concentration and Application Methods

Diesel Engine Cooling System Corrosion Inhibition

Add 810 directly to cooling system at a ratio of 1 pound per 20 gallons of cooling system water. 810 can be used in both open and closed recirculating systems. In closed cooling water systems, product life is normally indefinite.

Testing 810 Concentration Levels

The concentration of 810 can be tested by Seacole's Nitrite Test Kit or by electronic conductivity meters. Nitrite test readings should be in the range of 800 - 1800 ppm Nitrite. Conductivity test readings should be in the range of 4300 - 7000 micromohs.

Companion Products

See Seacole's Railroad and Heavy Equipment product line.

Safety and Handling

Read and understand this products MSDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

Ordering Information

810 is available in 50 pound pails and 398 pound drums.

13505 Industrial Park Blvd. Plymouth, MN 55441