

Technical Data Sheet

Seaclean 125B Beer Line Cleaner

Product Description

Seaclean 125B is a specially formulated alkaline cleaner for draft beer line cleaning. Seaclean 125B reduces surface tension between unwanted beer deposits. Seaclean 125B is a highly concentrated formula rendering low usage volume for greater economy. Seaclean 125B is dyed with a blue indicator to safely determine when Seaclean 125B is in the line and when it has been safely flushed out.

Performance Features

- Dyed Blue for Operator Safety
- Highly Concentrated For Greater Economy
- Cleans and Removes Unwanted Beer Deposits

Physical Specifications

Physical State	Liquid
Appearance	Blue
pH (Use Dilution)	> 13
Water Solubility	Complete
Rinseability	Excellent

Equipment Requirements

Seaclean 125B is safe for use in all beer line systems.

Product Make-Up

- 1. Fill tank $\frac{3}{4}$ full of clean water.
- 2. Add required amount of Seaclean 125 slowly. Heat may be generated during mixing. Refer to Concentration and Application Methods section.
- 3. Add water to level, mix well and heat to operating temperature.

Concentration and Application Methods

Beer Line Cleaning

Add 10 - 50 fl. oz of Seaclean 125B per gallon of water depending upon size and type of equipment.

<u>Time</u> 10 Minutes - 2 Times Per Month

Technical Data Sheet

Companion Products

See Seacole's Janitorial, Restaurant, and Building Maintenance Product Line.

Safety and Handling

Read and understand this products MSDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

Ordering Information

Seaclean 125B is available in 55 gallon drums.

13505 Industrial Park Blvd. Plymouth, MN 55441

Copyright ©2008 Seacole-CRC, LLC. All rights reserved. Seacole-C&H and Seacole-C&H Logos are registered trademarks of Seacole-CRC. All other marks are the property of their respective owners. The information and specifications in this data sheet are subject to change without notice. This product may be exported from the US only in accordance with the Export Administration Regulations established by the U.S. Department of Commerce, Bureau of Industry and Security.