



# Technical Data Sheet

Product Code: ACQ7753 Revised Date: 10/21/2024

## Dynamic Duo Kit

### Product Description

Dynamic Duo is an ultra-high pH, heavy-duty detergent engineered to attack grease, grime, soil or any other unwanted contaminants. Dynamic Duo is a super concentrated chemistry capable of cleaning industrial equipment, tankers, trucks, buses, and farm vehicles. Dynamic Duo will leave a streak free finish, brighter paint, clearer glass, and shiny wheels.

### Performance Features

- Quickly removes greases, oils, grime and other soils
- Contains no harmful glycol ethers, phosphates, HAPs, or VOCs
- Multi-metal safe
- Package as an EZ Kit to eliminate freight costs and storage requirements

### Physical Specifications

Physical State	Liquid
Appearance	Green
pH	≈13.5
Rinsability	Excellent

### Equipment Requirements

Dynamic Duo is safe for use with all standard cleaning equipment.

### Product Make-Up

Dynamic Duo is the concentrated version of Seacole's Evolution. Packaged as an EZ Kit with two parts. When both parts are combined Dynamic Duo can be diluted with water to make 30 gallons of Seacole's Evolution. **Dynamic Duo must be diluted with water prior to use.**

### Concentration and Application Method

#### Dilutions Requirements

**Dynamic Duo must first be diluted with water prior to use. Mix equal amounts of Part A and Part B together with 25 gallons of water. This solutions can then be used at different concentrations depending on application.**

#### General Maintenance

Use Dynamic Duo at a use concentration of 3%–20% by volume depending on the nature, make-up and extent of the soils to be removed. The use of HOT water increases performance. Apply to the surface to be cleaned with the desired application method. Follow with a thorough water rinse.

#### Mop/Bucket

For heavy duty shop floor cleaning, add 10%–20% by volume of Dynamic Duo to a mop bucket filled with HOT clean water. Apply to the surface to be cleaned with mop or brush. Where soil deposits are heavy, let soak for 5 to 15 minutes and brush if possible. Follow with additional mopping or a thorough hose or high- pressure water rinse. For additional soil removal, wet-vacuum dry-cleaned area.

#### Automatic Floor Scrubbers

For heavy duty shop floor & hard surface cleaning, add 10%–20% by volume of Dynamic Duo to the already water filled solution tank. Adding Dynamic Duo to the tank after filling with water will diminish foam production. Hot water temperatures for most plastic-tanked scrubbers should not exceed 140° F. Where soil deposits are heavy, a double pass may be necessary. Rinse with clean water. Operation of equipment should be done in accordance with the equipment manufacturer's instructions.

#### Sponge/Bucket Vehicle Washing



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | [seacole.com](http://seacole.com)





# Technical Data Sheet

For typical vehicle, truck or fleet washing, add 5%-10% by volume of Dynamic Duo to a water-filled bucket at a temperature between 40°–160° F. Apply to surface to be cleaned with sponge or brush. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse.

#### Low- or High-pressure Washer

Apply Dynamic Duo at a rate of 4–12 fl. ounces/gallon (ratios of 1:32–1:10). Apply to surface to be cleaned. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse.

#### Foaming Equipment

Dynamic Duo will create high quality foam through typical low- & high-pressure foam generators. Apply to surface to be cleaned. Allow foam to soak and cling to soils. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse. Chemical set-up and operation of equipment should be done in accordance with the equipment manufacturer's instructions.

#### **Companion Products**

For the nonconcentrated version of this product please see Seacole's Evolution. Please see Seacole Product Catalog.

#### **Safety and Handling**

Please review and understand the Dynamic Duo SDS before handling.

#### **Waste Treatment**

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations.

#### **Ordering Information**

Dynamic Duo is available as an EZ Kit containing 2 parts each packaged in either: 2.5-gallon jug, 5-gallon pails, 55-gallon drums, or 275-gallon totes.



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | [seacole.com](https://seacole.com)

