# **Technical Data Sheet**

Product Code: A585XXX Revised Date: 5/01/2025

# C&H 585

# **Product Description**

C&H 585 is a petroleum based liquid rust inhibitor designed to protect metal parts during prolonged indoor storage after manufacturing or machining. C&H 585 provides a transparent rust preventative film for easy visual inspection of identifying marks.

#### Performance Features

- Forms A Thin. Soft Protective Film That Will Not Run. Wick, or Crack When Dry
- · Provides Up to One Year or More of Indoor Rust Protection
- Passes A 40 Day Corrosion Test in A Standard 100°F 100% Humidity Cabinet Neutralizes Fingerprints to Prevent Fingerprint Corrosion
- Transparent Film Does Not Interfere with Visual Inspection of Parts or Reading of Identifying Marks
- Easily Applied by Dip, Brush, Low Pressure Spray or Wiping
- Can Be Diluted with Mineral Spirits If a Lighter Film Is Needed
- · Can Be Removed Easily with Solvents or Hot Alkaline Cleaning Compounds

# Physical Specifications

Physical State	Liquid
Appearance	Amber
рН	Neutral

### **Equipment Requirements**

C&H 585 is safe for use in all standard dip tanks and can be safely applied using a brush or low-pressure sprayer. Operation of equipment should be done in accordance with the equipment manufacturer's instructions.

#### **Product Make-Up**

C&H 585 is packaged ready-to-use. Do not dilute.

# **Concentration and Application Methods**

# Long Term Indoor Storage

Apply by dipping, brush, or low-pressure course spray or wiping. Saturate the surface of parts completely with C&H 585 after manufacturing or reworking processes. If applied by dip tank directly after a water-based wash or rinse step, water carried from parts to tank will separate to the bottom and can be removed by a bottom drain valve.

# Safety and Handling

Read and understand this product SDS before handling.

#### Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

# **Ordering Information**

C&H 585 is available in 55-gallon drums.



+1 (763) 582-1140 +1 (800) 966-2909 13505 Industrial Park Blvd. Plymouth, MN 55441 seacole.com

