



Technical Data Sheet

Product Code: ASPCWXX Revised Date: 5/01/2025

C&H Spraydet CW

Product Description

C&H Spraydet CW is a highly concentrated, multi-metal safe, alkaline liquid detergent engineered to produce superior cleaning results for the removal of the toughest contaminants; specifically synthetic cutting lubricants, oils, carbon deposits, cosmoline protective coatings, tenacious road film, and even printing inks.

Performance Features

- Quickly Removes Synthetic Cutting Lubricants, Oils, Carbon Deposits, Cosmoline Protective Coatings, Road Film, and Printing Inks
- Will NOT Attack the Base Metal of Parts Preserving Parts Dimensions
- Formulated with Advanced Anti-Foam & Corrosion Inhibitor Technology
- Excellent Rinse ability Leaving Parts Clean, Bright and Residue Free
- Contains NO Silicone Based Ingredients that Interfere with New Coatings or Paint
- Will NOT Darken or Turn Aluminum Black
- Contains NO VOC's or HAP's
- Biodegradable and Environmentally Green

Physical Specifications

Physical State	Liquid
Appearance	Amber
Rinseability	excellent
pH (use dilution)	11.5

Equipment Requirements

C&H Spraydet CW can be used in all aqueous heated high-pressure spray wash cabinet & conveyor systems, manual & automatic immersion / agitation / soak tank cleaning. Operation of equipment should be done in accordance with the equipment manufacturer's instructions.

Product Make-Up

C&H Spraydet CW is a highly concentrated liquid. Dilute to specified concentrations prior to use.

Concentration and Application Methods

Heavy Duty Cleaning

Add 3 – 5% of C&H Spraydet CW per gallon of water.

Calculation

C&H Spraydet CW volume needed (gallons) = Sump Capacity (gallons) x Desired Concentration (%)

Time

5 - 45 minutes depending on equipment type being used and level of concentration.

Temperature

140° - 210°F



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | seacole.com





Technical Data Sheet

Mixing Instructions

C&H Spraydet CW can be mixed readily into dip tanks. While the wash pump is activated, pour C&H Spraydet CW slowly over the pumps intake area and let mix for ten minutes. When adding C&H Spraydet CW over the pumps intake area, make sure water is below 80° to prevent hazardous spattering.

Concentration Management

Use Seacole's Titration Kit to calculate and maintain optimal bath concentrations.

Safety and Handling

Read and understand this product's SDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

Ordering Information

C&H Spraydet CW is available in 5 gallon pails, 55 gallon drums, and 275 gallon totes.



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | seacole.com

