

Technical Data Sheet

Product Code: A571XXX Revised Date: 5/01/2025

C&H 571

Product Description

C&H 571 is a highly concentrated liquid inorganic rust inhibitor engineered for all iron, steel, yellow and soft metal parts when additional corrosion, oxidation or rust protection is needed. C&H 571 is specifically designed to provide in-process rust protection and short-term indoor part storage. C&H 571 provides superior rust protection in wash and final rinse sections of all aqueous industrial parts washers from heated high-pressure spray cabinets and conveyorized systems to free standing manual and immersion type tanks.

Performance Features

- Highly Concentrated and Economical Formula Provides Low Volume Usage and Greater Economy
- Eliminates "Flash Rusting" of Parts After Process Cleaning Operations
- Provides in-Process Rust Protection for Parts Between Operations
- Provides Corrosion and Rust Protection for Parts Between Operations
- Excellent Rinseability Leaving Parts Clean, Bright, and Residue Free
- Contains NO Silicone Based Ingredients That Interfere With New Coatings or Paint
- Compatible with Automatic Replenishment Systems Biodegradable and Non-Hazardous
- Compatible With Most Alkaline Compounds When Simultaneous Use Is Required
- Does Not Contain Any Undissolved Particles To Plug Spray Nozzles Or Drain Systems

Physical Specifications

Physical State	liquid
Appearance	Clear, Water, White
Rinseability	excellent
% VOC/HAP	0%
pH (use dilution)	Approximately 9

Equipment Requirements

C&H 571 is safe for use in all standard mass finishing or process parts cleaning systems. Operation of equipment should be done in accordance with the equipment manufacturer's instructions.

Product Make-Up

C&H 571 is a concentrated industrial rust inhibitor. Dilute to specified strength concentrations.

Concentration and Application Methods

In-Process / Short Term

Use C&H 571 in the final rinse section after cleaning, deburring, descaling or burnishing operations. Add C&H 571 at 0.5% - 2.0% by total volume of water.

Pour the desired volume of C&H 571 directly into the circulating wash or final rinse sump. Allow C&H 571 to disperse between additions to prevent overuse.

Automatic Metering Pump

Greater economy and consistent rust protection can be achieved by automatically metering in small, predetermined amounts of C&H 571 into the wash or rinse sump or final rinse water supply line on a low dose, continuous basis.



+1 (763) 582-1140 | **+1 (800) 966-2909** | 13505 Industrial Park Blvd. Plymouth, MN 55441 |







Technical Data Sheet

Safety and Handling

Read and understand this product SDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

Ordering Information

C&H 571 is available in 4x1 cases, 5-gallon pails, and 55-gallon drums.



+1 (763) 582-1140 **+1 (800) 966-2909**

13505 Industrial Park Blvd. Plymouth, MN 55441

seacole.com



