



Technical Data Sheet

Product Code: A543AXX Revised Date: 5/01/2025

C&H 543A

Product Description

C&H 543A is a sheet metal forming lube designed to be used in a wide variety of applications and severities. It performs on both ferrous and non-ferrous metals and can be used for either stamping, punching, bending, or forming.

Performance Features

- Excellent Lubricity
- Good Rust Protection
- Capable of Being Cleaned Off Easily
- Contains NO VOC's Or HAP's

Physical Specifications

Physical State	Clear Viscous Liquid
Appearance	Red
pH	≈ Neutral
Rinseability	Excellent

Product Make-Up and Concentration

Use C&H 543A as is. Dilution can be tested for cost reduction; however, lubricity and rust protection is reduced.

Application Methods

Apply by flooding, immersion, brushing, or roll coating.

Safety and Handling

Read and understand this product SDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

Ordering Information

C&H 543A is available in 55-gallon drums and 275-gallon totes.



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | seacole.com

