



Technical Data Sheet

Product Code: AQ1245N Revised Date: 10/24/2025

Total

Product Description

Total is an aluminum safe multipurpose cleaner, and degreaser engineered to eliminate the need for multiple cleaning products. Total is a medium duty, super concentrated product capable of cleaning most hard surfaces.

Performance Features

- Contains no harmful glycol ethers, phosphates, HAP's, or VOC's
- Will not attack shop floor sealants

Physical Specifications

Physical State	Liquid
Appearance	Greenish Yellow
pH	12-12.5
Rinsability	Excellent

Equipment Requirements

Total can be used with any standard sprayer, steam cleaner, or pressure washer.

Product Make-Up

Total is a highly concentrated liquid cleaner and degreaser. Dilute prior to use.

Concentration and Application Method

General Maintenance

Use Total at a use concentration of 3%–5% by volume depending on the nature, make-up and extent of the soils to be removed. The use of HOT water increases performance. Apply to the surface to be cleaned with the desired application method. Follow with a thorough water rinse.

Shop Floors & Other Hard Surface

MOP & BUCKET: For shop floor cleaning, add 10%–20% by volume of Total to a mop bucket filled with HOT clean water. Apply to the surface to be cleaned with mop or brush. Where soil deposits are heavy, let soak for 5 to 15 minutes and brush if possible. Follow with additional mopping or a thorough hose or high-pressure water rinse. For additional soil removal, wet-vacuum dry-cleaned area.

Automatic Floor Scrubbers

AUTOMATIC FLOOR SCRUBBERS: For shop floor & hard surface cleaning, add 5%–10% by volume of Total to the already water filled solution tank. Adding Total to the tank after filling with water will diminish foam production. Hot water temperatures for most plastic-tanked scrubbers should not exceed 140° F. Where soil deposits are heavy, a double pass may be necessary. Rinse with clean water.

Auto/Locomotive/Heavy Equipment Manual Exterior Cleaning

LOW PRESSURE: Apply Total as a presoak by low pressure spray, foam, or brush at a dilution of 5 - 20% by volume. Scrub heavily soiled areas as needed. Follow with a high-pressure rinse.

HIGH PRESSURE: Apply Total at a 1 - 10% (1-12oz.) dilution rate with a high-pressure washer.

Companion Products

Please see Seacole's Industrial Cleaning Catalog.

Safety and Handling

Please review and understand the Total SDS before handling.



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | seacole.com





Technical Data Sheet

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations.

Ordering Information

Total is available in 4x1-gallon bottles, 5-gallon pails, 55-gallon drums, and 275-gallon totes. Tankers available upon request.



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | seacole.com

